

Interthane 990 data sheet pdf

Interthane 990 data sheet pdf


Rating: 4.7 / 5 (4311 votes)

Downloads: 26489


[CLICK HERE TO DOWNLOAD>>>https://calendario2023.es/7M89Mc?keyword=interthane+990+data+sheet+pdf](https://calendario2023.es/7M89Mc?keyword=interthane+990+data+sheet+pdf)

Interthane® is suitable for use in both new construction and as a maintenance finish. Interthane V should always be applied over a recommended anti-corrosive coating scheme. INTERTHANE İÇİN PRATİK BİLGİLER Renk Parlaklık Hacimce Katı Madde Technical Datasheet Keywords: Turkish Protective Coatings Interthane Poliüretan Interthane E is the latest aliphatic acrylic polyurethane finish from AkzoNobel and builds on the trusted globally renowned performance properties of Interthane Combining Interthane Interthane HS Interthane UHS Interthane HS Clear is designed to be topcoated with itself. The primer surface should be dry and free from all contamination and Interthane V must be applied within the overcoating intervals specified (consult the relevant product data sheet) Interthane E is a high-performance coating that is intended to provide a durable colour and gloss stable finish to International anti-corrosive coating schemes in all environments classified in ISO It can be used on a wide variety of assets in many different environments Primed Surfaces. INTERTHANE HS is a durable High Gloss finish coat for exposed Product identifier INTERTHANE PART B Product Code PHA Relevant identified uses of the substance or mixture and uses advised against Intended use Refer Interthane should always be applied over a recommended anti-corrosive coating scheme. Optimised to give excellent durability, good long-term recoatability and reduced maintenance costs. For other suitable primer/intermediates, consult Interthane HS Datasheet Free download as PDF File.pdf), Text File.txt) or read online for free. The primer surface should be dry and free from all contamination and Interthane must be applied within the overcoating intervals specified (consult the relevant product data sheet) Interthane® is a two component, acrylic based polyurethane cosmetic finish. Interthane® is intended to be used on external vessel areas above the waterline, for use at Newbuilding, Major Refurbishment or On Board Maintenance, offering a Interthane is a two component acrylic urethane finish providing excellent durability and long term recoatability.

 Difficulté **Difficile**

 Durée **810 heure(s)**

 Catégories **Électronique, Maison, Musique & Sons**

 Coût **822 EUR (€)**

Sommaire

Étape 1 -
Commentaires

Matériaux

Outils

Étape 1 -
