

Chain hoist pdf

Chain hoist pdf


Rating: 4.7 / 5 (3608 votes)

Downloads: 26685


CLICK HERE TO DOWNLOAD>>><https://myvroom.fr/7M89Mc?keyword=chain+hoist+pdf>

Widely used to improve the efficiency of material handling (and transportation). 3 tt. Hitachi chain hoist can be used for a wide range of purposes from Introduction. (kg) 3, lbs. Capacitylbs. (6, kg) H min. (3 m) lift Hitachi Electric Chain Hoist. (kg) 1, lbs. This manual cIX chain Hoist is an efficient lifting device for handling loads fromkg to 2, kg (capacity up to 5, kg available later). air hose assembly Founded in, The Hoist Manufacturers Institute (HMI), an affiliate of Material Handling Industry, is a trade association of manufacturers of overhead handling hoists. Connect hoist to nearest air source using a minimum 1/2" i.d. Obliquity of the hooks ton hoist differing in parts of chain and hook size. The chain hoist can only be put into operation when it is in good conditionBefore lifting, inspect the hooks to see whether they are securely attached. konecranes has built on ades of experience Electric Chain Hoist Operator's Manual/EN/ 3/This document and the information contained herein, is the exclusive property of R&M MATERIALS HANDLING, The beam on which the trolley is to be used must safely support the combined weight of the hoist, trolley and capacity load. Minimum turning radius of the trolley is" for 1/4 and 1/2 ton models;" forton models. Hoist frames are aluminum alloy. The products of its member companies include hand chain hoists, ratchet lever hoists, trolleys, air chain and air rope hoists, and electric chain and electric wire rope hoists Careful inspection should be made to the parts, such as hooks, load chain, braking device, etc., and the lubrication of the hoist. This manual is provided by Bison Lifting Equipment covering the safe operation and maintenance procedures for the Electric Chain Hoist. Rotate the suspension lug in°increments. For all models except spark resistant models; load chains are welded link type of To rotate the lug°for parallel mounting, follow instructions below: (1) On 1/4 throughton hoists, remove the two screws securing the anti-rotation bracket and remove the bracket. (3, kg), lbs. (kg) 1, lbs. Reinstall the anti-rotation bracket and secure with two screws and lock washers (1, kg) 6, lbs. Unit weight withft. The 3, 4,andton hoists are internally similar to the /2 and single load chainton hoists differing in parts of chain and hook size.

 Difficulté Facile

 Durée 483 minute(s)

 Catégories Énergie, Musique & Sons, Sport & Extérieur

 Coût 961 EUR (€)

Sommaire

Matériaux

Outils

Étape 1 -