

Concealed hinge template pdf

Concealed hinge template pdf


Rating: 4.9 / 5 (4996 votes)

Downloads: 4992

CLICK HERE TO DOWNLOAD>>><https://tds11111.com/7M89Mc?keyword=concealed+hinge+template+pdf>

Once you have the holes bored for the concealed hinges, The hinge is fixed on the door with two pre-mounted chipboard screws. c. Do not drill through door face. Q Choose TEMPLATES Concealed Geared Hinges Q All dimensions are measured in inches and [millimeters] from the top of the door to the centerline of the holes and bearings. Then predrill holes using a self-centering bit and finish with screws /2 to /2 from top or bottom of door, if third hinge for taller doors, third hinge is centered on door. Do not drill through 5 MM inset. Insert hinge into door and fasten with screws. Once you have the holes bored for the concealed hinges, simply place the hinge in the hole and square it up with a square or a straight edge on two hinges. Drill pilot holes for screws per template. adjusting the b. /2 to /2 from top or bottom of door, if third hinge for taller doors, third hinge is centered on door. Q HD geared templates Hinge model"" " EPT HD -FM-EPT TW8 HD concealedTWP HD concealedHD surfaceHD surfaceHD -FM-EPT TW8 HD concealed • Overall hinge lengthmm () Hinge widthmm () N on-handed Opening angledegrees •Dimensional adjustabilityVertical +/-mmHorizontal +/-mmDepth +/-mm For wood or hollow metal doors with wood or metal frames UL Listed for hollow metal, steel covered composite and Full Overlay European Concealed HingesInstalling Hinge to Door a. Glass door hinge cup The hinge is fixed into one single hole on the glass door. Q Choose location for EL prep from locations dimensioned. For Models SL, SL, SL, SL & SLfasteners EL LOCATIONS HOLES DO NOT SCALE DIMENSIONS: INCHES 5 MM inset. Glass thickness must be TEMPLATES Concealed Pin & Barrel Hinges Q All dimensions are measured in inches and [millimeters] from the top of the door to the centerline of the holes. Do not overtighten TEMPLATES Concealed Pin & Barrel Hinges Q All dimensions are measured in inches and [millimeters] from the top of the door to the centerline of the holes. Full Overlay European Concealed HingesInstalling Hinge to Door a. Drill holemm (15/32") deep for hinge cup per template usingmm boring bit. Drill holemm (15/32") deep for hinge cup per template usingmm boring bit. Do not drill through door face.

 Difficulté Moyen

 Durée 636 jour(s)

 Catégories Électronique, Maison, Musique & Sons

 Coût 860 EUR (€)

Sommaire

Étape 1 -
Commentaires

Matériaux

Outils

Étape 1 -
