

# Th400 manual pdf

Th400 manual pdf


Rating: 4.6 / 5 (1944 votes)

Downloads: 14743


CLICK HERE TO DOWNLOAD>>><https://calendario2023.es/QnHmDL?keyword=th400+manual+pdf>

Use care to avoid damaging the material where the bushing rides. Learn how to repair, overhaul, or service the Turbo Hydra-Matic transmission with this comprehensive manual. Find troubleshooting Estimated Reading Timesecs GM JP (Automatic Transmissions) Ltd Tel +(0)info@ TH (3L80) RWDSpeed Install new forward clutch piston inner lip seal in groove of forward clutch piston, with the lip facing in the direction shown in Figure Lubricate both seals with a small amount of DK TPCDK. (Does speedo work in forward gear?)Stator roller clutch damaged (Vehicle moves, but is very sluggish)Turbine hub splines stripped or brokenTurbine or pump vanes StepDrive New Bushing. This is a special hollow bolt; oil must flow through it to the intermediate clutch. Il and large accumulator rings, teflon or aluminum. (Figureservo assembly in the usual See Figures and Two different front servo assemblies are used in the TH This is covered in detail in the appropriate section of this manual Manual valve loose from rooster cone pinRooster cone nut loose on manual shaftInternal splines stripped or damagedDifferential damaged or axle broken. Note the depth of the old bushing and make sure to drive the new bushing to the same depth, and line up the lube oil hole at the same time. Put it in a safe place until reassembly of the unit Installation InstructionsWhitestone Road Baltimore, MD () FAX: () TH INTERNAL TRANSBRAKEPart REAR SERVORemove and discard sm. Use fine-grit automotive sandpaper Remove Oil Pump, Manual Shaft and Speedometer Gear Housing StepRemove Oil Pump, Manual Shaft and Speedometer Gear Housing. Contains: Deep Chrome Pan Pickup Tube () D DSleeve () D NOTES Transtar Industries, Inc. No part of this The Transmission Parts WarehouseAutomatic ChoiceGM Remove the front servo piston, washer, and servo pin from the front servo bore, followed by the spring retainer and spring. Use a sharp-angle cut punch to catch the edge of the old bushing and remove it. Using a point 3/8-inch socket, remove the center support retaining bolt.

 Difficulté Difficile

 Durée 306 jour(s)

 Catégories Art, Vêtement & Accessoire, Électronique, Énergie, Bien-être & Santé

 Coût 295 USD (\$)

## Sommaire

Étape 1 -

Matériaux

Outils

---

Étape 1 -

---